

Amana Models	Electric Heat Models				Heat Pump Models	
	AE093E35AXAA	AE123E35AXAA	AE183E35AXAA	AH093E35AXAA	AH123E35AXAA	AH183E35AXAA

General Features:

Voltage	230/208	230/208	230/208	230/208	230/208	230/208
Discharge Air	Top	Top	Side	Top	Top	Side
Auto Air Swing	No	No	Yes	No	No	Yes
Slide-out Filter	Side Pull-out	Side Pull-out	Front Pull-out	Side Pull-out	Side Pull-out	Front Pull-out
Approx. Chassis Wgt.	88 lbs	91 lbs	132 lbs	91 lbs	96 lbs	143 lbs
Approx. Shipping Wgt.	108 lbs	111 lbs	151 lbs	111 lbs	116 lbs	162 lbs

Cooling:

Capacity / BTUH	9,500 / 9,200	11,600 / 11,200	17,800 / 17,400	9,500 / 9,200	11,600 / 11,200	17,300 / 17,000
Amps	4.3 / 4.5	5.2 / 5.7	8.2 / 8.8	4.6 / 4.8	5.5 / 5.9	8.5 / 9.0
Watts	950 / 920	1,160 / 1,120	1,835 / 1,795	950 / 920	1,220 / 1,180	1,920 / 1,890
CFM	280	280	450	280	280	590
E.E.R.	10.0 / 10.0	10/10	9.7 / 9.7	10.0 / 10.0	9.5 / 9.5	9.0 / 9.0
Dehumidification - pts/hr	2.3	2.6	4.2	2.2	2.5	4.1

Electric Heat:

Capacity / BTUH	10,700 / 8,500	10,700 / 8,500	11,000 / 9,000	10,700 / 8,500	10,700 / 8,500	11,000 / 9,000
Amps	16.0 / 14.6	16.0 / 14.6	16.0 / 15.6	16.0 / 14.6	16.0 / 14.6	16.0 / 15.6
Watts	3,575 / 2,765	3,575 / 2,765	3,555 / 2,900	3,575 / 2,765	3,575 / 2,765	3,555 / 2,900

Heat Pump: (Reverse cycle)

Capacity / BTUH	n/a	n/a	n/a	8,400 / 8,100	10,300 / 10,000	16,000 / 15,700
Amps	n/a	n/a	n/a	4.2 / 4.5	5.1 / 5.6	8.3 / 8.8
Watts	n/a	n/a	n/a	850 / 820	1,160 / 1,130	1,800 / 1,770
C.O.P	n/a	n/a	n/a	2.9 / 2.9	2.6 / 2.6	2.6 / 2.6
Adjustable Change-Over Thermostat	n/a	n/a	n/a	n/a	n/a	n/a
Thermostatic Drain Valve	n/a	n/a	n/a	Yes	Yes	Yes

Dimensions:

Outer case-sleeve						
Height	15 3/8"	15 3/8"	16 7/8"	15 3/8"	15 3/8"	16 7/8"
Width	22 5/8"	22 5/8"	26"	22 5/8"	22 5/8"	26"
Depth	24"	24"	27 3/4"	24"	24"	30 1/2"
Depth with Front	26 3/4"	26 3/4"	29 3/4"	26 3/4"	26 3/4"	32 1/2"

Features: (all models)

Electrical	4.0' LCDI power cord; Perpendicular plug; 20-amp circuit breaker
Agency Approval	U.L. (Under Writers Laboratory) listed; USA and Canada
Chassis type	Slide-out for easy installation and service accessibility
Fan Speeds	3 speeds, High, Medium and Low
Fan ONLY	Yes – High, Medium and Low speed
Condensate drain	Yes – condensate drain spout on the wall sleeve
Window kit	Yes – optional window mount kits are available

1-Year Entire Unit Limited Warranty*

5-Year Sealed System Limited Warranty*

1-Year entire unit and 5-Year sealed system components. Goodman Company L.P. will repair or replace any factory defective part or sealed system leak caused by a defective part and pay labor and associated services costs directly related to the part. See product warranty for complete details.

*Complete warranty details available from your local dealer or at www.amana-ptac.com

Plug Type

Perpendicular
20 Amps
250 Volts



TWS TRANSWORLD
COMMERCIAL PRODUCTS DISTRIBUTORS

For more information, contact:
1.800.424.8550
sales@twsdistributors.com